

# ATS Balance Testing and Correction







# **ATS Balance Testing and Correction**

# **Balance Testing**

Balance testing measures the imbalance location of the part while spinning the part at speeds up to 220 KRPM while measuring G-levels at both ends of a shaft. Sensing of the imbalance location is done through analysis using NVH software integrated into the balance machine.

Software is capable of doing 1st,2nd & 3rd order analysis of imbalance and additional orders if required.

System is capable of monitoring and stopping the test under potentially destructive fail conditions such as excessive g-level, over temperature, over speed, etc.

# **Correction System**

Correction systems work in conjunction with balance testing to automatically remove material from a location identified by an imbalance tester. The Imbalance location is automatically provided by the balance tester. A touch less sensor system identifies location for material removal.

Software shall monitor and detect a successful material removal process by monitoring force applied while removing material through use of a 0-100 N load cell.

# **Products Tested Include**

• Rotating motor components



# Balance Tester

# **Capabilties**

- Speed ranging up to 220 KRPM
- Force measurements up to 250 G

# **Tests Performed**

- Measure G-levels of imbalance
- NVH (Noise, Vibration, harshness) Testing

#### **Correction System**

### **Capabilities**

- Axial material removal within +/- 15 degrees of imbalance location
- Programmable material removal control, 0.1 to 1.5 mm in depth based on magnitude of material removal required to achieve a balanced system

Contact ATS directly for custom or product specific applications beyond the scope of this document.



Tel: 1-(905)-850-8600 ext. 83279 Fax: 1-(905)-850-9336 Send e-mail to: atstest@atsautomation.com or visit our web site at: www.atsautomation.com

© 2015 ATS, and other designated trademarks used are a trademark of ATS Automation Tooling Systems Inc. All rights reserved. Please note, technical specifications are subject to change. Any third party trademarks referenced herein are the property of their respective owners. September 2015